

2024-11-18 Using Slings for Lifting

A sling is a type of device manufactured specifically to lift and move heavy loads, such as construction materials or machinery. It consists of a length of sturdy material, such as nylon webbing, wire rope, or chain, with loops or hooks at each end. The sling is attached to the load to be lifted, and attached to a hoisting mechanism, such as a crane or winch.

There are several different types of slings available, including single-leg slings, multi-leg slings, and adjustable.

Single-leg slings have only one leg, while multi-leg slings have two or more legs that come together at a central point, such as a lifting eye. Adjustable slings can be adapted to fit the size of the load being lifted.

Here are some general guidelines for using a sling for lifting:

- Always determine the weight and size of the load to be lifted. This will help make sure you choose a sling with adequate strength and length for the job.
- Select the appropriate sling for the load and hoisting mechanism. Make sure the sling is rated for the weight of the load and configuration used and is made of a material suitable for the job.
- Inspect the sling for any damage or wear. Look for frayed edges, cuts, burns, broken wires or stitching, or other damage that could compromise the strength of the sling. Also make sure tags displaying the sling's lifting capacity are attached and legible. NEVER use a damaged sling.
- Position the sling around the load. Make sure the sling is evenly distributed around the load, and that it is not twisted or tangled. Protect the sling from sharp edges on the load when necessary.
- Attach the hooks or loops of the sling to the hoisting mechanism. Make sure the hooks are securely fastened and that the sling is positioned so the load is properly balanced.
- Test the load before lifting. Gently tug on the sling to make sure it and the load are secure.
- Slowly lift the load using the hoisting mechanism. Make sure to keep the load level and stable.
- Move the load to the desired location. Use the hoisting mechanism to carefully move the load to its destination. Use a tag line, when necessary, to maintain safe clearance from the moving load.
- Lower the load. Slowly lower the load to the ground or support surface, making sure to keep it level and stable. Do not let the load crush the sling on the ground or cribbing.
- Disconnect the sling from the hoisting mechanism and remove it from the load. Carefully disconnect and remove the sling from around the load.

Do not use the hoist to pull the sling from under the load. Return it to its designated storage area when done. It's important to follow all applicable manufacturer's safety guidelines when using a sling for lifting. It's also necessary for inexperienced workers to have a trained

operator or supervisor on hand to oversee the lifting process and ensure that it is done safely and efficiently.

By Clicking "Mark as Read" - you are acknowledging you have read this entire (opened appropriate attachments) Toolbox Talk and understand this is company policy and will abide by regulations outlined in this safety policy. Please complete your acknowledgement within 24 hours of release. If you receive this notice, you are REQUIRED to read this content.

Revision #1

Created 25 November 2024 14:58:13 by Dale Bergman

Updated 25 November 2024 14:58:45 by Dale Bergman